



DC Inverter Hi-Wall Split Systems



Exclusively distributed by



DC Inverter Hi-Wall Split Systems



Reliable home comfort and advanced efficiency

Stylishly designed and quiet during operation, a Lennox hi-wall air conditioner (heat pump) will complement your décor and your lifestyle. Incorporating the latest energy-saving technology and variable speed motor, the Lennox DC Inverter range achieves and maintains the desired temperature quickly and more efficiently than conventional models.

So the only thing you'll notice is a comfortable indoor climate that's cool in summer, cosy in winter and economical to enjoy regardless of the season. And because it's from Lennox, you can be sure of superior quality that won't break the budget. It's just another way that Lennox climate control solutions allow you to live smart and keep your cool.

Enhanced Comfort Control

Improves comfort levels by compensating the set point to account for the difference between ceiling and floor temperatures.

Even Air Distribution

Air distribution is improved by directing air horizontally during cooling and downwards in heating.

Active Carbon Filter

Eliminates certain kinds of odours such as ammonia and deactivates harmful chemical gases like formaldehyde. It also traps small duct particles, smoke and pet fur preventing allergic reactions.

Anti-corrosion Condenser Fins

The outdoor coil is treated to improve fin corrosion resistance and heat transfer for longer life and improved performance.

Turbo Mode

Cooling and heating rates are increased to achieve the desired set temperature quicker.

Auto-restart Function

Restarts and resumes the previous operating mode automatically if the power supply is interrupted during operation.

Sleep Mode

After the set temperature is attained, the Lennox DC Inverter Split maintains the set temperature by automatically adjusting itself thereby providing energy savings and more consistent comfort levels.

LENNOX DC INVERTER HI-WALL SPLIT SYSTEM													
MODEL NUMBER	INDOOR/ OUTDOOR	LNINVE026-D	LNINVC026-D	LNINVE035-D	LNINVC035-D	LNINVE052-D	LNINVC052-D	LNINVE063-D	LNINVC063-D	LNINVE070-D	LNINVC070-D	LNINVE080-D	LNINVC080-D
SET NUMBER		LNINV2610-D		LNINV3510-D		LNINV5210-D		LNINV6310-D		LNINV7010-D		LNINV8010-D	
PERFORMANCE		COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING
Capacity (min-max)	kW	2.6 (0.35 - 3.0)	2.8 (0.75 - 3.5)	3.50 (0.95 - 4.0)	3.85 (0.88 - 4.30)	5.2 (0.65 - 6.00)	5.85 (0.9 - 7.00)	6.3 (0.7 - 7.0)	6.3 (0.95 - 8.0)	7.0 (1.4 - 8.7)	7.5 (1.05 - 10.0)	8.0 (1.4 - 8.7)	8.4 (1.05 - 10.0)
Input Power	kW	0.73	0.78	0.98	1.07	1.59	1.79	1.93	1.93	2.14	2.30	2.46	2.55
AEER/ACOP*	W/W	3.82	3.97	3.69	3.72	3.31	3.38	3.28	3.36	3.37	3.39	3.35	3.45
Star Rating*		2.5	2.5	2.5	2.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Indoor Air Flow	L/S	161 / 138 / 111 / 83		167 / 138 / 111 / 83		236 / 216 / 180 / 152		263 / 222 / 194 / 152		305 / 295 / 265 / 250		333 / 305 / 277 / 250	
Sound Pressure Level	SH / H / M / L dB(a) Outdoor dB(a)	40 / 37 / 35 / 32 50		42 / 39 / 36 / 33 52		46 / 44 / 40 / 35 56		51 / 45 / 42 / 39 56		51 / 47 / 43 / 40 59		51 / 48 / 43 / 40 59	
Operating Range	Cooling (C°) Heating (C°)	18 to 43 -7 to 24		18 to 43 -7 to 24		18 to 43 -7 to 24		18 to 43 -7 to 24		18 to 43 -7 to 24		18 to 43 -7 to 24	
ELECTRICAL		LNINV2610-D		LNINV3510-D		LNINV5210-D		LNINV6310-D		LNINV7010-D		LNINV8010-D	
Volts/Phase/Hz	V / Φ / Hz	240 / 1 / 50		240 / 1 / 50		240 / 1 / 50		240 / 1 / 50		240 / 1 / 50		240 / 1 / 50	
Rated Running Current	A	3.2	3.5	4.3	4.7	7.05	7.94	8.56	8.56	10.08	10.76	10.91	11.31
Max Current	A	7.2		9		11.8		11.98		16.1		15.97	
INSTALLATION		LNINV2610-D		LNINV3510-D		LNINV5210-D		LNINV6310-D		LNINV7010-D		LNINV8010-D	
Unit Dimensions (w x h x d)	Indoor (mm) Outdoor (mm)	845 x 275 x 180 776 x 540 x 320		845 x 275 x 180 848 x 592 x 320		940 x 298 x 200 955 x 700 x 396		1007 x 315 x 219 955 x 700 x 396		1178 x 326 x 253 980 x 790 x 427		1178 x 326 x 253 980 x 790 x 427	
Weight	Indoor (kg) Outdoor (kg)	11 / 14 32 / 36		11 / 14 36 / 39		13 / 17 44 / 49		16 / 21 50 / 55		17.5 / 23.5 65 / 73		17.5 / 23.5 70 / 75	
Refrigerant	R410A (g)	870		1260		1200		1900		1800		2400	
Pre-charged length	M	7.5		7.5		7.5		7.5		7.5		7.5	
Additional Charge	g/M	20		20		20		30		30		50	
Max Pipe Run	M	15		20		20		25		25		30	
Max Elevation	M	10		10		10		10		10		10	
Moisture Removal	L/h	0.8		1.2		1.8		2.5		2.5		2.7	
Pipe Sizes - Liquid/ Suction	mm(inch")	φ6.35/φ9.52(1/4"/3/8")		φ6.35/φ12.7(1/4"/1/2")		φ6.35/φ12.7(1/4"/1/2")		φ6.35/φ16(1/4"/5/8")		φ6.35/φ16(1/4"/5/8")		φ6.35/φ16(1/4"/5/8")	
Application Area**	m ²	12 - 18		16-24		23-34		32-50		35-52		36-54	

*In accordance with AS/NZS 3823.1.1 and AS/NZS 3823.2 Standards
**Subject to heat load calculations

australia
13 23 50
lennoxus.com.au

new zealand
0800 653 330
lennoxnz.co.nz



© and ™ Registered Trade Mark and Trade Mark of Heatcraft Australia Pty Ltd © Copyright 2017 Heatcraft Australia Pty Ltd.
The contents of this brochure are copyright protected and may not be reproduced in any form without the written consent of Heatcraft. Recommendations and advice regarding the use of the products described in this publication are to be taken as a guide only and are given without liability on the part of the company or its employees. As Heatcraft continually improves its product range and processes, Heatcraft reserves the right to change product specifications without any prior notification. Please refer to the Heatcraft website for the latest version of this publication. The purchaser should independently determine the suitability of the product for the intended use and application and that the product complies with relevant standards. Heatcraft accepts no responsibility for loss or damage (direct or indirect and including consequential loss, loss of profits or opportunity and economic loss) however arising which results from any errors or omissions in the information contained in this publication or arising from the use or application of the information contained herein.